

**TECHNICAL DATA STATIONARY MIXERS
DOUBLE AUGER MODEL**

STANDARD FEATURES

2 Auger thickness 15mm
 Tank bottom thickness 20mm
 Tank wall thickness 8mm
 2 manual counter-knives h=450mm (17-24m³)
 2 hydraulic counter-knives h=900mm (27-30m³)
 Chassis with 4 support columns on the ground and with 4 weights sensors Ø70mm
 Perin weighing system 800
 Rh side discharge door
 Hydraulic system quick joints
 2 speed gear box 1000 rpm
 Cardan shaft
 Simple inspection ladder
 Inspection bonnet designed for platform and ladder

MODELS

	SL-170	SL-200	SL-220	SL-240	SL-270	SL-300
Weight	7.600 kg	7.800 kg	8.300 kg	8.500 kg	9.000 kg	9.300 kg
Capacity	17 m ³	20 m ³	22 m ³	24 m ³	27 m ³	30 m ³
Max load	6.000 kg	7.000 kg	7.700 kg	8.400 kg	10.800 kg	12.000 kg
No. Knives	16	16	20	20	24	24
KW	75	75	90	90	110	110

DIMENSIONS

	SL-170	SL-200	SL-220	SL-240	SL-270	SL-300
A Length	7050	7050	7250	7250	7400	7400
A1 Length	8500	8500	8700	8700	8900	8900
B Width	2650	2650	2950	2950	2950	2950
C Height	2580	2670	2780	2930	3140	3320

